
Technical Notes: DLA 32cc



32cc Gas Engine Specifications:

DLA 32cc (1.97 in³) Gas Engine

Power: Displacement:	3.8 HP @ 8200 rpm 32 cc (1.97 in ³)			
Idle Speed:	1700 rpm			
Static Thrust:	19.4 pounds @ 100 m (~328 ft Altitude) (Pulling Force)			
	17.2 pounds @ 1800 m (~5,900 ft Altitude)			
Propellers (Recommended):	18 x 8 / 10, 19 x 8, 20 x 8			
RPM Range:	1700 – 8300 rpm			
Carburetor:	Tillotson ™, HU-134A (Typ), Diaphragm Pump			
Spark Plug:	CM-6 Special			
Muffler Volume:	32.23 cc (1.97 in ³)			
Cylinder Diameter (Bore) Stroke:	37 mm / 30 mm (1.46 in / 1.18")			
Compression Ratio:	7.6:1			
Gas	87 – 89 Octane, unleaded ("Regular")			
Gas : Oil Ratios:	30 – 40:1 Break-in Trial Run; 40 – 50 : 1 Normal Flying			
Weights:	Engine: 32.1 oz, Muffler: 2.3 oz, Ignition: 3.5 oz			
	(Total: $37.9 \text{ oz} = 3.37 \text{ lbs}$)			
Ignition:	Fully Advancing, Auto, <u>Capacitive</u> <u>D</u> ischarge <u>Ignition</u>			
Ignition Power:	6.6 to 8.4 VDC			

Support Information:

Ignition Battery:

Break-in Propeller (Suggested) Intake Manifold: Items Included in Retail Pkg: 2-S, LiPo, 2,100—mAh (Typical) Unregulated
6-S, NiMH, 2,100—mAh (Typical)
18 x 8
4-Leaf Reed Valve, V-Configuration
Engine, Muffler / Gasket & Bolts, CD Ignition, Sparkplug,
Stand-off Mounts (Machined), Operations Manual (on Website),
Bolts–Mounting.

	Mount Dimensions		Mounting	Stand Offa	Drop Polto	Muffler Bolts
DLA	X (mm)	Y (mm)	Bolts	Stand-Offs	Prop Bolts	Mumer Doits
32cc	70	54	5.0 x 0.8 - 20 mm	11.3 OD x 65 L mm	4.0 x 0.7 - 35 mm	5.0 x 0.8 - 16 mm

Suggested Items:

Gas Tank Fuel Point[™] (From Golden Skies R/C) Gas Line (From Golden Skies R/C) Ignition Kill Switch (From Golden Skies R/C) Propeller 2-Cycle Oil Gas Line Filter Mounting Template Propeller Drill-bit Guide (From Golden Skies R/C) **Torque Wrench** Spinner Battery, Ignition Tachometer